

Product Overview

The CMD290 is a wideband GaN MMIC distributed low noise amplifier die which operates from 2 to 26 GHz. The broadband device is ideally suited for applications requiring low noise figure performance and high input power survivability. The CMD290 delivers 12.5 dB of gain with a corresponding noise figure of 2.3 dB and an output 1 dB compression point of +19 dBm at 13 GHz. The CMD290 features an RF input survivability of 2 Watts. The amplifier is a 50 ohm matched design which eliminates the need for external DC blocks and RF port matching. The CMD290 offers full passivation for increased reliability and moisture protection.


Key Features

- Ultra Wideband Performance
- Low Noise Figure
- High RF Power Survivability
- Low Current Consumption
- Small Die Size

Ordering Information

Part No.	Description
CMD290	10 pcs in gel pack

Functional Block Diagram



Note: V_{gg2} is optional for gain control

Electrical Performance ($V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$, $T_A = 25^\circ\text{ C}$, $F = 13\text{ GHz}$)

Parameter	Min	Typ	Max	Units
Frequency Range		2 - 26		GHz
Gain		12.5		dB
Noise Figure		2.3		dB
Input Return Loss		23		dB
Output Return Loss		23		dB
Output P1dB		19		dBm
Output IP3		27		dBm
Output IP2		29		dBm
Supply Current		100		mA

Absolute Maximum Ratings

Parameter	Rating
Drain Voltage, V_{dd}	30 V
Gate Voltage, V_{gg}	-8 V to -1 V
RF Input Power	+33 dBm
Channel Temperature, T_{ch}	200° C
Power Dissipation, P_{diss}	28.75 W
Thermal Resistance, Q_{JC}	4° C/W
Operating Temperature	-55 to 85° C
Storage Temperature	-55 to 150° C

Exceeding any one or combination of the maximum ratings may cause permanent damage to the device.

Recommended Operating Conditions

Parameter	Min	Typ	Max	Units
V_{dd}	10	20	28	V
I_{dd}		100		mA
V_{gg}		-3		V


Electrical performance is measured at specific test conditions. Electrical specifications are not guaranteed over all recommended operating conditions.

Electrical Specifications ($V_{dd} = 20$ V, $V_{gg} = -3$ V, $T_A = 25^\circ$ C)


Parameter	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	Units
Frequency Range		2 - 8		8 - 18			18 - 26			GHz
Gain	9	12.5		9.5	12.5		9.5	13.5		dB
Noise Figure		3.5	4.5		2.3	3.3		3.5	5.1	dB
Input Return Loss		20			15			10		dB
Output Return Loss		9			18			15		dB
Output P1dB		19.5			18			15		dBm
Output IP3		28.5			28					dBm
Output IP2		31			32					dBm
Supply Current	70	100	130	70	100	130	70	100	130	mA
Gain Temperature Coefficient		0.022			0.025			0.034		dB/°C
Noise Figure Temperature Coefficient		0.011			0.011			0.014		dB/°C

Typical Performance

Broadband Performance, $V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$, $I_{dd} = 100\text{ mA}$, $T_A = 25^\circ\text{ C}$




Narrow-band Performance, $V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$, $I_{dd} = 100\text{ mA}$, $T_A = 25^\circ\text{ C}$




Typical Performance

Gain vs. Temperature, $V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$




Gain vs. V_{dd} , $V_{gg} = -3\text{ V}$, $T_A = 25^\circ\text{ C}$




Typical Performance

Noise Figure vs. Temperature, $V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$




Noise Figure vs. V_{dd} , $V_{gg} = -3\text{ V}$, $T_A = 25^\circ\text{ C}$




Typical Performance

P1dB vs. Temperature, $V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$




P1dB vs. V_{dd} , $V_{gg} = -3\text{ V}$, $T_A = 25^\circ\text{C}$




Typical Performance

Psat vs. Temperature, $V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$




Psat vs. V_{dd} , $V_{gg} = -3\text{ V}$, $T_A = 25^\circ\text{ C}$




Typical Performance

Output IP3 vs. Temperature, $V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$




Output IP3 vs. V_{dd} , $V_{gg} = -3\text{ V}$, $T_A = 25^\circ\text{ C}$




Typical Performance

Output IP2 vs. Temperature, $V_{dd} = 20\text{ V}$, $V_{gg} = -3\text{ V}$




Output IP2 vs. V_{dd} , $V_{gg} = -3\text{ V}$, $T_A = 25^\circ\text{ C}$




Typical Performance

Drain Current vs. Drain Voltage, $V_{gg} = -3\text{ V}$, $T_A = 25^\circ\text{ C}$



Mechanical Information

Die Outline (all dimensions in microns)




Notes:

1. No connection required for unlabeled pads
2. Backside is RF and DC ground
3. Backside and bond pad metal: Gold
4. Die is 100 microns thick
5. DC bond pads (2, 3, 5, 6) are 100 x 100 microns
6. RF bond pads (1, 4) are 100 x 100 microns

Pad Description

Pad Diagram



Functional Description

Pad	Function	Description	Schematic
1	RF in	DC blocked and 50 ohm matched	
2	V _{dd}	Power supply voltage Decoupling and bypass caps required	
3	V _{gg2}	Optional supply voltage for gain control Decoupling and bypass caps required Pin must be left open if unused	
4	RF out	DC blocked and 50 ohm matched	
5	ACG	Low frequency termination Attach bypass capacitor per application circuit	
6	V _{gg}	Power supply voltage Decoupling and bypass caps required	
Backside	Ground	Connect to RF / DC ground	

Applications Information


Assembly Guidelines

The backside of the CMD290 is RF ground. Die attach should be accomplished with electrically and thermally conductive epoxy or eutectic attach. Standard assembly procedures should be followed for high frequency devices. The top surface of the semiconductor should be made planar to the adjacent RF transmission lines, and the RF decoupling capacitors placed in close proximity to the DC connections on chip.

RF connections should be made as short as possible to reduce the inductive effect of the bond wire. Use of a 0.8 mil thermosonic wedge bonding is highly recommended as the loop height will be minimized. The RF input and output require a double bond wire as shown.

The semiconductor is 100 μm thick and should be handled by the sides of the die or with a custom collet. Do not make contact directly with the die surface as this will damage the monolithic circuitry. Handle with care.


Assembly Diagram



GaAs MMIC devices are susceptible to damage from Electrostatic Discharge. Proper precautions should be observed during handling, assembly and test.

Applications Information

Application Circuit



Biasing and Operation

The CMD290 is biased with a positive drain supply and a negative gate supply. Performance is optimized when the drain voltage is set to +20 V, though it may be set between +10 V and +28 V. The nominal gate voltage is -3 V.

Turn ON procedure:

1. Apply gate voltage V_{gg} and set to -5 V
2. Apply drain voltage V_{dd} and set to +20 V
3. Increase V_{gg} (less negative) to achieve a drain current of 100 mA

Turn OFF procedure:

1. Turn off drain voltage V_{dd}
2. Turn off gate voltage V_{gg}

RF power can be applied at any time.

Handling Precautions

Parameter	Rating	Standard
ESD – Human Body Model (HBM)	Class 1A	ESDA / JEDEC JS-001-2012



Caution!
ESD-Sensitive Device

RoHS Compliance

This part is compliant with 2011/65/EU RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

This product also has the following attributes:

- Lead Free
- Antimony Free
- TBBP-A (C₁₅H₁₂Br₄O₂) Free
- SVHC Free
- PFOS Free
- Halogen Free



Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations:

Web: www.qorvo.com

Tel: 1-844-890-8163

Email: customer.support@qorvo.com

Important Notice

The information contained in this Data Sheet and any associated documents (“Data Sheet Information”) is believed to be reliable; however, Qorvo makes no warranties regarding the Data Sheet Information and assumes no responsibility or liability whatsoever for the use of said information. All Data Sheet Information is subject to change without notice. Customers should obtain and verify the latest relevant Data Sheet Information before placing orders for Qorvo® products. Data Sheet Information or the use thereof does not grant, explicitly, implicitly or otherwise any rights or licenses to any third party with respect to patents or any other intellectual property whether with regard to such Data Sheet Information itself or anything described by such information.

DATA SHEET INFORMATION DOES NOT CONSTITUTE A WARRANTY WITH RESPECT TO THE PRODUCTS DESCRIBED HEREIN, AND QORVO HEREBY DISCLAIMS ANY AND ALL WARRANTIES WITH RESPECT TO SUCH PRODUCTS WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, USAGE OF TRADE OR OTHERWISE, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Without limiting the generality of the foregoing, Qorvo® products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death. Applications described in the Data Sheet Information are for illustrative purposes only. Customers are responsible for validating that a particular product described in the Data Sheet Information is suitable for use in a particular application.

© 2020 Qorvo US, Inc. All rights reserved. This document is subject to copyright laws in various jurisdictions worldwide and may not be reproduced or distributed, in whole or in part, without the express written consent of Qorvo US, Inc. | QORVO® is a registered trademark of Qorvo US, Inc.