


54/7400 ✓ 011065
 54H/74H00 ✓ 011069
 54S/74S00 ✓ 011574
 54LS/74LS00 ✓ 011068

QUAD 2-INPUT NAND GATE


CONNECTION DIAGRAMS PINOUT A



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		V _{CC} = +5.0 V ±5%, T _A = 0° C to +70° C	V _{CC} = +5.0 V ±10%, T _A = -55° C to +125° C	
Plastic DIP (P)	A	7400PC, 74H00PC 74LS00PC, 74S00PC		9A
Ceramic DIP (D)	A	7400DC, 74H00DC 74LS00DC, 74S00DC	5400DM, 54H00DM 54LS00DM, 54S00DM	6A
Flatpak (F)	A	74LS00FC, 74S00FC	54LS00FM, 54S00FM	3I
	B	7400FC, 74H00FC	5400FM, 54H00FM	

PINOUT B



INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	1.25/1.25	0.5/0.25
Outputs	20/10	12.5/12.5	25/12.5	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74		54/74H		54/74S		54/74LS		UNITS	CONDITIONS	
		Min	Max	Min	Max	Min	Max	Min	Max			
I _{CC} H	Power Supply	8.0		16.8		16		1.6		mA	V _{IN} = Gnd	V _{CC} = Max
I _{CC} L	Current	22		40		36		4.4			V _{IN} = Open	
t _{PLH}	Propagation Delay	22		10		2.0	4.5	10		ns	Figs. 3-1, 3-4	
t _{PHL}		15		10		2.0	5.0	10				

*DC limits apply over operating temperature range; AC limits apply at T_A = +25° C and V_{CC} = +5.0 V.